

Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

**AMENDMENTS TO THE CLAIMS**

1. (Previously Presented) A reconfigurable organic light-emitting device, comprising:  
at least two organic light-emitting layers; and  
at least one high-energy-gap carrier-blocking layer, formed between each of the organic light-emitting layers;

wherein the organic light-emitting layers and the high-energy-gap carrier-blocking layer can be heated to induce the inter-diffusion process, so as to change the structure of the reconfigurable organic light-emitting device and emit light of different spectra in different structures.

2. (Previously Presented) The organic light-emitting device as recited in claim 1, further comprising an upper electrode and a lower electrode sandwiching the organic light-emitting layers and the high-energy-gap carrier-blocking layer, wherein by applying a bias voltage thereon, the reconfigurable organic light-emitting device may emit lights.

3. (Previously Presented) The organic light-emitting device as recited in claim 2, further comprising a light-to-heat conversion layer adjacent to at least one of the organic light-emitting layers, wherein by shining a light-beam thereon, the reconfigurable organic light-emitting device may be heated.

4. (Previously Presented) The organic light-emitting device as recited in claim 2, further comprising a built-in resistive heating electrode adjacent to at least one of the organic light-

Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

emitting layers, wherein by applying a current thereon, the reconfigurable organic light-emitting device may be heated.

5. (Previously Presented) The organic light-emitting device as recited in claim 2, further comprising an external heating source adjacent to at least one of the organic light-emitting layers.

6. (Original) The organic light-emitting device as recited in claim 5, wherein the external heating source is a patterned resistive heating electrode, wherein by applying a current thereon, the reconfigurable organic light-emitting device may be heated.

7. (Original) The organic light-emitting device as recited in claim 4, wherein the built-in resistive heating electrode is a patterned resistive conductor.

8. (Original) The organic light-emitting device as recited in claim 3, wherein the light-beam is a laser beam.

9. (Previously Presented) The organic light-emitting device as recited in claim 1, wherein a glass transition temperature of the high-energy-gap carrier-blocking layer is smaller than the glass transition temperatures of the organic light-emitting layers.

Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

10. (Original) The organic light-emitting device as recited in claim 1, wherein the emission spectrum of the reconfigurable organic light-emitting device is one of the characteristic spectra of the at least two organic light-emitting layers, and when the structure of the reconfigurable organic light-emitting device is changed, the emission spectrum of the reconfigurable organic light-emitting device changes from the characteristic spectrum of one layer of the at least two organic light-emitting layers to that of another layer of the at least two organic light-emitting layers.

11. (Currently Amended) A display apparatus employing ~~an~~ a reconfigurable organic light-emitting device, comprising:

a lower electrode;

a layer of ~~a~~ the reconfigurable organic light-emitting device formed on the lower electrode; and

an upper electrode formed on the layer of the reconfigurable organic light-emitting device; ~~the structure of the layer of the reconfigurable organic light-emitting layer device being~~ locally reconfigured via a patterned heating source, and by applying a bias voltage between the upper electrode and the lower electrode, light of different spectra in different structures being emitted.

12. (Currently Amended) The display apparatus as recited in claim 11, wherein structure of the layers-layer of the reconfigurable organic light-emitting device further comprises: at least

Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

two organic light-emitting layers; and at least one high-energy-gap carrier-blocking layer, formed between each of the organic light-emitting layers.

13. (Previously Presented) The display apparatus as recited in claim 12, wherein a glass transition temperature of the high-energy-gap carrier-blocking layer is smaller than the glass transition temperatures of the organic light-emitting layers.

14. (Previously Presented) The display apparatus as recited in claim 12, wherein the emission spectrum of the reconfigurable organic light-emitting device is one of the characteristic spectra of the at least two organic light-emitting layers, and the emission spectrum of the reconfigurable organic light-emitting device is changed from the characteristic spectrum of one layer of the at least two organic light-emitting layers to another layer of the at least two organic light-emitting layers when the reconfigurable organic light-emitting device changes its structure.

15. (Currently Amended) The display apparatus as recited in claim ~~11~~12, further comprising a light-to-heat conversion layer adjacent to at least one of the organic light-emitting layers, wherein by shining a light-beam thereon, the reconfigurable organic light-emitting device may be heated.

16. (Currently Amended) The display apparatus as recited in claim ~~11~~12, further comprising an external heating source adjacent to at least one of the organic light-emitting layers, by which the reconfigurable organic light-emitting device may be heated.

Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

17. (Currently Amended) The display apparatus as recited in claim ~~11~~12, further comprising ~~a~~at least one built-in resistive heating electrode adjacent to at least one of the organic light-emitting layers, wherein by applying a current thereon, the reconfigurable organic light-emitting device may be heated.

18. (Original) The display apparatus as recited in claim 17, wherein the lower electrode may be used on the built-in resistive heating electrode

19. (Original) The display apparatus as recited in claim 11, wherein the bias voltage applied between the upper electrode and the lower electrode is within the range of 2 volts to 15 volts.

20. (Currently Amended) A display apparatus employing ~~an~~a reconfigurable organic light-emitting device, comprising:

a substrate;

a lower electrode formed on the substrate;

an insulating layer formed on the lower electrode;

an upper electrode separating island formed on the insulating layer;

a layer of ~~a~~the reconfigurable organic light-emitting device formed on the lower electrode, the insulating layer, and the upper electrode separating island; and

Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

an upper electrode formed on the layer of the reconfigurable organic light-emitting device; wherein the structure of the layer of the reconfigurable organic light-emitting device can be reconfigured via a patterned heating source, and by applying a bias voltage between the upper electrode and the lower electrode, light of different spectra in different structures can be emitted.

21. (Original) The display apparatus as recited in claim 20, wherein the layer of the reconfigurable organic light-emitting device further comprises: at least two organic light-emitting layers; and at least one high-energy gap carrier-blocking layer, formed between each of the organic light-emitting layers.

22. (Previously Presented) The display apparatus as recited in claim 21, wherein a glass transition temperature of the high-energy-gap carrier-blocking layer is smaller than the glass transition temperatures of the organic light-emitting layers.

23. (Previously Presented) The display apparatus as recited in claim 21, wherein the emission spectrum of the reconfigurable organic light-emitting device is one of the characteristic spectra of the at least two organic light-emitting layers, and the emission spectrum of the reconfigurable organic light-emitting device is changed from the characteristic spectrum of one layer of the at least two organic light-emitting layers to that of another layer of the at least two organic light-emitting layers when the reconfigurable organic light-emitting device changes its structure.

Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

24. (Previously Presented) The display apparatus as recited in claim 21, further comprising a light-to-heat conversion layer adjacent to at least one of the organic light-emitting layers, wherein by shining a light-beam thereon, the reconfigurable organic light-emitting device may be heated.

25. (Original) The display apparatus as recited in claim 24, wherein the light-beam is a laser beam.

26. (Original) The display apparatus as recited in claim 24, wherein the light-to-heat conversion layer is any one of the upper electrode and the lower electrode.

27. (Original) The display apparatus as recited in claim 24, wherein the light-to-heat conversion layer is formed outside of the upper electrode and the lower electrode.

28. (Original) The display apparatus as recited in claim 24, wherein the light-to-heat conversion layer is formed between the upper electrode and the lower electrode.

29. (Previously Presented) The display apparatus as recited in claim 21, further comprising a built-in resistive heating electrode adjacent to at least one of the organic light-emitting layers, wherein by applying a current thereon, the reconfigurable organic light-emitting device may be heated.

Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

30. (Original) The display apparatus as recited in claim 29, wherein the built-in resistive heating electrode is a layer of patterned resistive conductor.

31. (Original) The display apparatus as recited in claim 30, wherein the layer of patterned resistive conductor is any one of the upper electrode and the lower electrode.

32. (Original) The display apparatus as recited in claim 30, wherein the layer of patterned resistive conductor is formed outside of the upper electrode and the lower electrode.

33. (Previously Presented) The display apparatus as recited in claim 24, further comprising an external heating source adjacent to at least one of the organic light-emitting layers.

34. (Original) The display apparatus of claim 33, wherein the external heating source is a layer of patterned resistive conductor, wherein by applying a current thereon, the reconfigurable organic light-emitting device may be heated.

35. (Original) The display apparatus as recited in claim 20, wherein the upper electrode and the lower electrode by vertically cross each other.

36. (Currently Amended) A display apparatus employing ~~an~~ a reconfigurable organic light-emitting device, comprising:



Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

a substrate;

a lower electrode formed on the substrate;

an insulating layer formed on the lower electrode;

a layer of ~~a~~ the reconfigurable organic light-emitting device formed on the lower electrode and the insulating layer;

an upper electrode formed on the layer of the reconfigurable organic light-emitting device; and

a transistor circuit electrically connected with the upper electrode and the lower electrode; wherein the structure of the layer of the reconfigurable organic light-emitting device is reconfigured via a patterned heating source, and by applying a bias voltage between the upper electrode and the lower electrode, controlled by the transistor circuit, light of different spectra in different structures is emitted.

37. (Previously Presented) The display apparatus as recited in claim 36, wherein the layer of the reconfigurable organic light-emitting device further comprising:

at least two organic light-emitting layers; and

at least one high-energy-gap carrier-blocking layer, formed between each of the organic light-emitting layers.

38. (Previously Presented) The display apparatus as recited in claim 37, wherein a glass transition temperature of the high-energy-gap carrier-blocking layer is smaller than the glass transition temperatures of the organic light-emitting layers.

Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

39. (Previously Presented) The display apparatus as recited in claim 37, wherein the emission spectrum of the reconfigurable organic light-emitting device is one of the characteristic spectra of the at least two organic light-emitting layers, and the emission spectrum of the reconfigurable organic light-emitting device is changed from the characteristic spectrum of one layer of the at least two organic light-emitting layers to that of another layer of the at least two organic light-emitting layers when the reconfigurable organic light-emitting device changes its structure.

40. (Previously Presented) The display apparatus as recited in claim 37, further comprising a light-to-heat conversion layer adjacent to at least one of the organic light-emitting layers, wherein by shining a light-beam thereon, the reconfigurable organic light-emitting device may be heated.

41. (Original) The display apparatus as recited in claim 40, wherein the light-beam is a laser beam.

42. (Currently Amended) The display apparatus as recited in claim 40, wherein the light-to-heat conversion layer is disposed on any at least one of the upper electrode and the lower electrode.

Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

43. (Original) The display apparatus as recited in claim 40, wherein the light-to-heat conversion layer is formed outside of the upper electrode and the lower electrode.

44. (Original) The display apparatus as recited in claim 40, wherein the light-to-heat conversion layer is formed between the upper electrode and the lower electrode.

45. (Previously Presented) The display apparatus as recited in claim 37, further comprising a built-in resistive heating electrode adjacent to at least one of the organic light-emitting layers, wherein by applying a current thereon, the reconfigurable organic light-emitting device may be heated.

46. (Previously Presented) The display apparatus as recited in claim 45, wherein the built-in resistive heating electrode is a layer of patterned resistive conductor.

47. (Original) The display apparatus as recited in claim 46, wherein the layer of patterned resistive conductor is outside of the lower electrode.

48. (Previously Presented) The display apparatus as recited in claim 37, further comprising an external heating source adjacent to at least one of the organic light-emitting layers.

Application No. 10/642,745  
Amendment dated February 21, 2006  
Reply to Office Action of October 18, 2005

Docket No.: 0698-0156P

49. (Original) The display apparatus of claim 48, wherein the external heating source is a layer of patterned resistive conductor, wherein by applying a current thereon, the reconfigurable organic light-emitting device may be heated.